

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-31206164-MG256k/128kVSAT

```
_ 0 X
cmd - Atalho
Microsoft Windows [versão 6.1.7601]
Copyright (c) 2009 Microsoft Corporation. Todos os direitos reservados.
 C:\Windows\System32>tracert 8.8.8.8
Rastreando a rota para google-public-dns-a.google.com [8.8.8.8]
com no máximo 30 saltos:
                                                                                                                                                            Ε
         2268
762
1379
1093
815
                                                              10.29.11.209
10.10.11.2
                   ms
                                    ms
                                                     ms
    2345
                           1488 ms
                                             3616 ms
                   ms
                                                             10.10.11.191
10.10.12.2
200.143.6.130
h200-215-188-137.ipb.diveo.net.br [200.215.188.1
                           1533 ms
1691 ms
572 ms
                                            1638 ms
1460 ms
735 ms
                   ms
                   ms
                   ms
6
371
7
                                             2139
          1510
                           1903
                   ms
                                    ms
                                                      ms
          3693 ms
                           3483 ms
                                             2982 ms
                                                              200-147-28-145.static.uol.com.br [200.147.28.145
    8
               *
                           1500 ms
                                              868 ms
                                                              200-147-28-186.static.uol.com.br [200.147.28.186
    9
            690 ms
                           1085 ms
                                             1594 ms
                                                              50.252.40.189.isp.timbrasil.com.br [189.40.252.5
01
                                                              72.14.194.55
216.239.54.17
216.239.56.59
google-public-dns-a.google.com [8.8.8.8]
  10
                           1876 ms
                                             1433 ms
            864 ms
  11
12
                                              876
585
            680
                   ms
                                                      ms
            918
                             544
                   ms
                                    ms
                                                      ms
  13
            525
                             701 ms
                                             1078
                   ms
                                                     ms
Rastreamento concluído.
C:\Windows\System32>ping 8.8.8.8 -t
Disparando 8.8.8.8 com 32 bytes de dados:
Resposta de 8.8.8.8: bytes=32 tempo=922ms
Resposta de 8.8.8.8: bytes=32 tempo=595ms
Resposta de 8.8.8.8: bytes=32 tempo=1922ms
Resposta de 8.8.8.8: bytes=32 tempo=724ms
Resposta de 8.8.8.8: bytes=32 tempo=777ms
Resposta de 8.8.8.8: bytes=32 tempo=1541ms
Resposta de 8.8.8.8: bytes=32 tempo=8041ms
Resposta de 8.8.8.8: bytes=32 tempo=8041ms
                                                         tempo=922ms TTL=51
tempo=595ms TTL=51
tempo=1922ms TTL=51
                                                         tempo=1922ms TTL=51
tempo=724ms TTL=51
tempo=777ms TTL=51
tempo=1541ms TTL=51
tempo=804ms TTL=51
Resposta de 8.8.8.8: bytes=32 tempo=1137ms TTL=51
Resposta de 8.8.8.8: bytes=32 tempo=992ms TTL=51
Resposta de 8.8.8.8: bytes=32 tempo=941ms TTL=51
Resposta de 8.8.8.8: bytes=32 tempo=572ms TTL=51
Resposta de 8.8.8.8: bytes=32 tempo=572ms TTL=51
Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 11, Recebidos = 11, Perdidos = 0 (0% de
                         perda),
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 572ms, Máximo = 1922ms, Média = 993ms
 Control-C
 ^C
C:\Windows\System32>
015
                                          UIUO-PER-31026164-MG E.M SÃO JORGE ITAMARANDIBA MG 05/11/2
```

```
10.50.0.199 - PuTTY
Login: root
Password: 1Sat2vsat
SatLink 2000
- Main board ID 120026, Revision R6.2
- SW ID 120208, Revision 14.1.3 Build 75
# arp show
   NetAddr
                 State MacAddr
   10.29.11.210 Dynamic 00:26:55:6c:b1:ac 1
# device show
System Information:
              : VIVO-PER-31206164
: Itamarandiba - MG
    Name
                         : VIVO-PER-31206164-MG
    Location
    Contact
   System Up time : 0 days, 00:54:46
                        : 13%
   CPU Load
    System time(UTC) : 05 November 2015 14:38:01
    Broadcast Message : not set
HW:
    Model
                         : SatLink 2000
                        : 120033
    HW ID
    Main board ID : 120026 R6.2
MAC addresses:
    Ethernet (LAN) : 00:20:0e:10:5c:64
Satellite (DVB) : 00:20:0e:10:5c:64
    Ethernet (LAN)
# arp show
   NetAddr State MacAddr
   10.29.11.210 Dynamic 00:26:55:6c:b1:ac 1
# dvb tx show
Satellite (DVB) TX Configuration
______
Auto start : Enabled IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm EIRP : 48.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
State : On (TDMA)
IDU Output Power : -23.0 dBm
ODU Output Power : 33.4 dBm
EIRP : 46.7 dBW
```

```
: 14.0 dB
Header Compression : Disabled
Timing correction : -149 us (261587 us)
Frequency correction: -300 Hz
# dvb rx show
Satellite (DVB) RX Configuration
______
Auto start : Enabled
Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)
                  : 15 minute
RX watchdog
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
Satellite (DVB) Receiver Status
_____
           : On
: Forward link up
Rx State
DVB State
                   : 1326, GlobalIP@Telstar-14R
Network
Frequency : 12.055946 GHz
Symbol Rate : 9.320062 Msps
S2 ModCod
   - receiving : 14 8PSK-3/4
     - current max : 23 16APSK-9/10
             : On
Pilot
Frame length
                  : Short
DVB S2 Mode
                  : ACM
                  : 0.25
Roll off
SNR : 14.0 dB Input Power : -21 dBm
IP DVB 10.50.0.199/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=840 ms
64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=720 ms
64 bytes from 8.8.8.8: time=600 ms
64 bytes from 8.8.8.8: time=840 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 600/720/840 ms
```