

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-22065733-PI

Link kbps
256k/128k

Plataforma
VSAT



```
Telnet 10.29.37.57
Login: Password:
SatLink 2000
- Main board ID 120026, Revision R6.2
- SW ID 120200, Revision 16.0.1 Build 57
Satellite (DUB) TX Configuration
Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz
ATM mode : UC-Mux
Header Compression : None
Satellite (DUB) Transmitter Status
State : On (DUB-RCS2)
IDU Output Power : -14.0 dBm
EIRP : 13.5 dB
Header Compression : Disabled
Timing correction : -46 us (252903 us)
Frequency correction: 150 Hz
```

```
Telnet 10.29.37.57
BK watchdog : 15 minute

Idx Pri SynchRate[Mbps] Freq[GHz] Mode PopId SatId Pwr SatName
Name Enable
= 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E
Yes

Satellite (DVB) Receiver Status
Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.059051 GHz
Symbol Rate : 15.000010 Mbps
S2 ModCod
- receiving : 10 16APSK-2/3
- current max : 20 16APSK-4/5
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 13.7 dB
Input Power : -35 dBm
#
```

```
cmd - Atalho
Resposta de 0.0.0.0: bytes=32 tempo=551ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=623ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=706ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=787ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=506ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=593ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=668ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=739ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=686ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=523ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=610ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=1531ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=957ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=674ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=747ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=827ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=544ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=628ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=699ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=647ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=847ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=564ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=642ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=722ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=804ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=524ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=600ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=676ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=754ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=846ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=555ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=635ms TTL=55
Resposta de 0.0.0.0: bytes=32 tempo=716ms TTL=55

Estatísticas do Ping para 0.0.0.0:
Pacotes: Enviados = 82, Recebidos = 82, Perdidos = 0 (0% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 506ms, Máximo = 1531ms, Média = 702ms
Control-C
^C
C:\Windows\System32>arp -a

Interface: 10.29.37.50 --- 0x13
Endereço IP Endereço físico Tipo
10.29.37.57 00-20-0e-10-0e-0c dinâmico
10.29.37.63 ff-ff-ff-ff-ff-ff estático
224.0.0.2 01-00-5e-00-00-02 estático
224.0.0.251 01-00-5e-00-00-0f estático
224.0.0.252 01-00-5e-00-00-0c estático
239.255.255.250 01-00-5e-7f-ff-fa estático
255.255.255.255 ff-ff-ff-ff-ff-ff estático

C:\Windows\System32>
C:\Windows\System32>U100-PER 22065733-PI - E.R JOAQUIM MAIA - REDEÇÃO DO CURGU
EIA-PI
```