


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Cunha Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-26037351-PE
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : max
EIRP : max

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -11.2 dBm
ODU Output Power : 34.2 dBm
EIRP : 47.5 dBW
Es/No : 12.5 dB
Header Compression : Disabled

Timing correction : -47 us (249737 us)

Frequency correction: -90 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E

Yes

1 1 9.320000 12.055825 DVB-S2 4 0 0.0 E

Yes

* 6 6 25.333333 12.050000 DVB-S2 102 0 0.0 E

Yes

7 7 30.000000 12.050000 DVB-S2 102 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.049908 GHz
Symbol Rate : 25.332840 Msps

S2 ModCod

- receiving : 20 16APSK-4/5 - current max : 20 16APSK-4/5

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 13.3 dB
Input Power : -23 dBm

