

## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-25090100-PB256/128VSAT



dvb tx show

## Satellite (DVB) TX Configuration

-----

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 32.3 dBm
EIRP : 45.6 dBW
Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

## Satellite (DVB) Transmitter Status

-----

State : On (DVB-RCS)
IDU Output Power : -21.6 dBm
ODU Output Power : 32.3 dBm
EIRP : 45.6 dBW
Es/No : 13.0 dB
Header Compression : Disabled

Timing correction : -155 us (262475 us)

Frequency correction: -30 Hz

#

# dvb rx show

Satellite (DVB) RX Configuration -----

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

\* 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E

Yes

Satellite (DVB) Receiver Status \_\_\_\_\_

Rx State : On
DVB State : Forward link up : 1326, T14R Beam Network Frequency : 12.055752 GHz Symbol Rate : 9.320106 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 16 8PSK-8/9

rilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Strong DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 14.2 dB Input Power : -32 dBm

IP DVB 172.18.131.63 /32