


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira

Cliente: Vivo

Empresa
EMC Brasil
VIVO-PER-24071722-RN
256K/128K
VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -15 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 33.7 dBm

EIRP : 47.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -18.1 dBm ODU Output Power : 33.7 dBm EIRP : 47.0 dBW Es/No : 12.0 dB

Header Compression : Disabled

Timing correction : -56 us (250126 us)

Frequency correction: -110 Hz

dvb rx show

Satellite (DVB) RX Configuration _____

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
1	1	30.000000	12.050000	DVB-S2	4	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status _____

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.049916 GHz

Symbol Rate : 25.333050 Msps

S2 ModCod

- receiving : 19 16APSK-3/4 - current max : 20 16APSK-4/5

Pilot : On
Frame length : Short
DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 14.3 dB Input Power : -26 dBm

