

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho. Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23268565-CE
 256k/128k
 VSAT



dvb tx show Satellite (DVB) TX Configuration ______ Auto start : Enabled IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm Default CW Frequency: 0.000000 GHz ATM mode : VC-Mux Header Compression : None Satellite (DVB) Transmitter Status -----State : On (DVB-RCS2) IDU Output Power : -19.9 dBm Es/No : 14.5 dB Header Compression : Disabled Timing correction : -98 us (254332 us) Frequency correction: 30 Hz # dvb rx show Satellite (DVB) RX Configuration Auto start : Enabled Max Traffic MODCOD : 23 16APSK-9/10 RX watchdog : 15 minute Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable * 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E Yes Satellite (DVB) Receiver Status ______ : On : Forward link up : 1326, T14R Bear Rx State DVB State Network : 1326, T14R Beam : 12.059062 GHz : 15.000061 Msps Frequency Symbol Rate S2 ModCod - receiving : 18 16APSK-2/3 - current max : 22 16APSK-8/9 Pilot : On

Frame length : Shown DVB S2 Mode : ACM

IP DVB 172.18.133.16 /32

Roll off

SNR

DVB S2 Stream type : MPEG-TS

Input Power : -34 dBm

: Short

: 0.20

: 15.4 dB