TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Jefferson de Souza Marques | **Cliente: VIVO**

Empresa	VSAT-ID	Link kbps	Plataforma
EMC Brasil	VIVO-PER-31076619-MG	256/128	VSAT


```
Satellite (DVB) RX Configuration
--------------------------------
Auto start          : Enabled
Max MODCOD          : 23   16APSK-9/10 (SNR threshold: 23.5 dB)
RX watchdog         : 15 minute

Idx  Pri  SymbRate[Msps]  Freq[GHz]  Mode    PopId    Enable
* 0  0      9.320000      12.055825  DVB-S2  4          Yes

Satellite (DVB) Receiver Status
--------------------------------
Rx State            : On
DVB State           : Forward link up
Network             : 1326,  GlobalIP@Telstar-14R
Frequency           : 12.055743 GHz
Symbol Rate         : 9.319829 Msps
S2 ModCod
      - receiving   : 13   8PSK-2/3
      - current max : 23   16APSK-9/10
Pilot               : On
Frame length        : Short
DVB S2 Mode         : ACM
Roll off            : 0.25
SNR                 : 14.6 dB
Input Power         : -26 dBm
```

```
Satellite (DVB) TX Configuration
--------------------------------
Auto start          : Enabled
IDU Output Power    : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power    : 33.7 dBm
EIRP                : 47.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode            : VC-Mux
Header Compression  :  None


Satellite (DVB) Transmitter Status
--------------------------------
State               : On (TDMA)
IDU Output Power    : -24.1 dBm
ODU Output Power    : 33.5 dBm
EIRP                : 46.8 dBW
Es/No               : 15.0 dB
Header Compression  : Disabled
Timing correction   : -184 us (262600 us)
Frequency correction: -170 Hz
#


IP DVB 10.53.0.111/32


# ping 8.8.8.8
64 bytes from 8.8.8.8: time=960 ms
64 bytes from 8.8.8.8: time=780 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=760 ms
64 bytes from 8.8.8.8: time=730 ms

--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received,  0.00 percent packet loss
rtt min/avg/max = 700/780/960 ms
#
```