

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-23038535-CE256k/128kVSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.0 dBm
EIRP : 47.0 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -15.6 dBm
ODU Output Power : 34.2 dBm
EIRP : 47.2 dBW
Es/No : 10.5 dB
Header Compression : Disabled

Timing correction : -45 us (249446 us)

Frequency correction: 20 Hz

dvb rx show

Satellite (DVB) RX Configuration ______ Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name
Enable									
0	0	15.000000	12.059000	DVB-S2	102	0	0.0 E		
Yes									
1	1	9.320000	12.055825	DVB-S2	4	0	0.0 E		
Yes									
* 6	6	25.333333	12.050000	DVB-S2	102	0	0.0 E		
Yes									
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E		
Yes									

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Bear

Frequency : 12.049984 GHz

Symbol Rate : 25.333061 Msps : 1326, T14R Beam

S2 ModCod

- receiving : 7 QPSK-3/4 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 14.7 dB Input Power : -24 dBm

```
cmd - Atalho
    atísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 138, Recebidos = 136, Perdidos = 2 (1% de
perda),
oxinar un número redondo de vezes en milissegundos:
Mínino = 555ms, Máxino = 3518ms, Média = 1156ms
rrol-C
```