


TERMO DE ACEITE TÉCNICO


Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23142790-CE
 256k/128k
 VSAT





```
Telnet 10.29.40.185
                                                                                                                                                                                                                     -32 dBs
    atellite (DVB) RX Configuration
   Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
   RX watchdog
   Idx Pri SymbRate[Msps] Freq[GHz] Mode Popld SatId Pos SatName
* 0 0 15.000000 12.0550000 DVB-S2 102 0 0.0 E
1 1 9.320000 12.055025 DVB-S2 4 0 0.0 E
                                                                                                                                                        Name
                                                                                                                                                                                        Enable
                                                                                                                                                                                         Ves
   Satellite (DVB) Receiver Status
   Rx State
                                    : Forward link up
: 1326, T14R Beam
: 12.058866 GHz
: 15.000025 Msps
   Metwork
Frequency
Symbol Rate
    ymbol hate

2 ModCod

- receiving : 7 QPSK-3/4

- current max : 20 16APSK-4

Viot
Pilot
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 8.28
seg : 14.2 dB
                                                     16APSK-4/5
```

```
Resposta de 8.8.8.8: bytes=32 tempo=123ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=123ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=716ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=2388ms TTL=55
Resposta de 8.8.8.8: bytes=22 tempo=2388ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=180ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=122ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=180ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=380ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=370ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo
```