


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira

Cliente: Vivo

Empresa VSAT-ID Link kbps Plataforma
EMC Brasil VIVO-PER-23060115-CE 256K/128K VSAT



Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -15 dBm IDU Max Output Power: 0.0 dBm

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -15.1 dBm Es/No : 13.5 dB Header Compression : Disabled

Timing correction : 38 us (248784 us)

Frequency correction: 240 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

PV watchdar

: 15 minute RX watchdog

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable * 0 0 30.000000 12.050000 DVB-S2 102 0 0.0 E Yes 0 1 1 0.0 E Yes

Satellite (DVB) Receiver Status

: On Rx State

DVB State : Forward link up Network : 1326, T14R Beam : 12.049934 GHz Frequency : 29.999648 Msps Symbol Rate

S2 ModCod

- receiving : 13 8PSK-2/3 - current max : 22 16APSK-8/9

: On Pilot Frame length : Short DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS

Roll off : 0.20 SNR : 15.7 dB Input Power : -35 dBm

