

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira


Cliente: Vivo

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-26071550-PE

Link kbps
256K/128K

Plataforma
VSAT



dvb tx show

Satellite (DVB) TX Configuration

```
-----
Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.0 dBm
EIRP                 : 46.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
-----
State                : On (DVB-RCS2)
IDU Output Power     : -17.9 dBm
ODU Output Power     : 32.7 dBm
EIRP                 : 45.7 dBW
Es/No                : 11.0 dB
Header Compression   : Disabled
Timing correction    : -91 us (251226 us)
```

Frequency correction: -140 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msp/s]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050162 GHz
Symbol Rate : 25.332725 Msp/s
S2 ModCod
- receiving : 20 16APSK-4/5
- current max : 20 16APSK-4/5
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 14.2 dB
Input Power : -25 dBm

SatLink VSAT

10.29.60.105/wmi/dwp/index_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

ODU Serial Number

ODU HW Version

SatLink 2000

16.0.1.57

00:20:0e:10:55:4e

00:20:0e:10:55:4e

0 days, 00:11:30

22%

VIVO-PER-26071550-PE

Salgadinho - PE

104804040203090306860000

4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

CMD - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=592ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=729ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=748ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=857ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=599ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=623ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1386ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2443ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=770ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=729ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=870ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=559ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=604ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=674ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=721ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=798ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=875ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=590ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=644ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=730ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=782ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=870ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=573ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=606ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=674ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=742ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=848ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=887ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=574ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=629ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=672ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=732ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=799ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=860ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2156ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1903ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=820ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1907ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1304ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2128ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=649ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=590ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2130ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=907ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1431ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1123ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=730ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=576ms TTL=44

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 149, Recebidos = 147, Perdidos = 2 (1% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 559ms, Máximo = 2971ms, Média = 1020ms
Control-C
C:\Windows\System32>

11:10

19/08/2017