

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Henrique Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-31022098-MG256k/128kVSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : max
EIRP : max

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
IDU Output Power : -15.7 dBm
ODU Output Power : 35.1 dBm
EIRP : 48.1 dBW
Es/No : 11.0 dB
Header Compression : Disabled

Timing correction : -150 us (251160 us)

Frequency correction: 40 Hz

dvb rx show

Satellite (DVB) RX Configuration _____

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 25.333333 12.050000 DVB-S2 102 0 0.0 E

Yes

1 1 30.000000 12.050000 DVB-S2 4 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Bear

Frequency : 12.050105 GHz

Symbol Rate : 25.333139 Msps : 1326, T14R Beam

S2 ModCod

- receiving : 7 QPSK-3/4 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stroom DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 14.6 dB Input Power : -22 dBm

