


STM/Vodanet

TERMO DE ACEITE TÉCNICO

VSAT

Solicitante: SES – Secretaria de Estado de Saúde de Minas Gerais

NOC/Operadora: Ermínio Alves Ribeiro Junior Operadora/Cliente: Gilvan Junior Responsável/cliente: Eder Leal GRE/Prodemge: Aguinaldo de Matos Consórcio VSAT-ID Porta kbps **Plataforma**



Satellite (DVB) RX Configuration _____

: Enabled

Auto start

Max MODCOD : 15 8PSK-5/6 (SNR threshold: 10.6 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 45.000000 11.606250 DVB-S2 3 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 65281, Prodemge@Vodanet

Frequency : 11.606163 GHz Symbol Rate : 44.999513 Msps

S2 ModCod

- receiving : 4 QPSK-1/2 - current max : 14 8PSK-3/4

: On Pilot Frame length : Short

DVB S2 Mode : ACM

Roll off : 0.20

SNR : 12.0 dB Input Power : -33 dBm

```
Satellite (DVB) TX Configuration
_____
Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.2 dBm
                : 46.5 dBW
EIRP
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : UDP/IP/DSM-CC
Satellite (DVB) Transmitter Status
______
State : On (TDMA)

IDU Output Power : -18.7 dBm

ODU Output Power
ODU Output Power : 33.1 dBm
EIRP : 46.4 dBW
Es/No
               : 12.5 dB
Header Compression : DSM-CC
Timing correction : 34 us (252852 us)
Frequency correction: -210 Hz
IP DVB: 10.148.6.142/32
Pinging 10.174.217.1 with 32 bytes of data:
Reply from 10.174.217.1: bytes=32 time=582ms TTL=62
Reply from 10.174.217.1: bytes=32 time=584ms TTL=62
Reply from 10.174.217.1: bytes=32 time=597ms TTL=62
Reply from 10.174.217.1: bytes=32 time=600ms TTL=62
Reply from 10.174.217.1: bytes=32 time=551ms TTL=62
Reply from 10.174.217.1: bytes=32 time=615ms TTL=62
Reply from 10.174.217.1: bytes=32 time=628ms TTL=62
Reply from 10.174.217.1: bytes=32 time=544ms TTL=62
Reply from 10.174.217.1: bytes=32 time=547ms TTL=62
Reply from 10.174.217.1: bytes=32 time=560ms TTL=62
Ping statistics for 10.174.217.1:
  Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 544ms, Maximum = 628ms, Average = 580ms
```