

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Jefferson de Souza Marques Cliente: VIVO

> **Empresa VSAT-ID** Link kbps **Plataforma EMC Brasil** VIVO-PER-31130397-MG 256/128 **VSAT**



Satellite (DVB) RX Configuration

Auto start : Enabled

: 23 16APSK-9/10 (SNR threshold: 23.5 dB) Max MODCOD

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

: 12.055849 GHz Frequency Symbol Rate : 9.319974 Msps

S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 15 8PSK-5/6

Pilot : On Frame length : Short DVB S2 Mode : ACM Roll off : 0.25 SNR : 14.5 dB Input Power : -24 dBm

```
Satellite (DVB) TX Configuration
-----
Auto start : Enabled IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
                  : 47.0 dBW
EIRP
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)

IDU Output Power : -27.0 dBm

ODU Output Power : 33.8 dBm
EIRP
                   : 47.1 dBW
Es/No
                   : 14.1 dB
Header Compression : Disabled
Timing correction : -197 us (262473 us)
Frequency correction: -140 Hz
IP DVB 10.53.0.151/32
#ping 8.8.8.8
64 bytes from 8.8.8.8: time=740 ms
64 bytes from 8.8.8.8: time=920 ms
64 bytes from 8.8.8.8: time=1090 ms
64 bytes from 8.8.8.8: time=740 ms
64 bytes from 8.8.8.8: time=1110 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 740/910/1110 ms
```