EMC EMERGING MARKETS COMMUNICATIONS	**TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais			
NOC/Operador: Guilherme Henrique		**Cliente: VIVO**	
Empresa EMC Brasil	**VSAT-ID** VIVO-PER-27018750-AL	**Link kbps** 256k/128k	**Plataforma** VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -23 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.0 dBm
EIRP : 47.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -20.2 dBm
ODU Output Power : 33.7 dBm
EIRP : 46.7 dBW
Es/No : 1.5 dB
Header Compression : Disabled
Timing correction : -70 us (255492 us)
Frequency correction: 100 Hz
dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name	Enable
* 0	0	15.000000	12.059000	DVB-S2	102	0	0.0 E			Yes
1	1	9.320000	12.055825	DVB-S2	4	0	0.0 E			Yes

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.059216 GHz
Symbol Rate : 14.999946 Msps
S2 ModCod
- receiving : 15 8PSK-5/6
- current max : 20 16APSK-4/5
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 14.1 dB
Input Power : -23 dBm


SatLink VSAT
10.29.47.73/wmi/dwp/index_page.dwp
SatLink VSAT
Status
Satellite
Statistics
Device
DHCP
Eventlog
Configuration
Satellite
IP
Static NAT
Lineup
Device
Help
Introduction
Device Status
Model
SatLink 2000
Software Version
16.0.1.57
LAN MAC Address
00:20:0e:10:63:91
DVB MAC Address
00:20:0e:10:63:91
System Up Time
0 days, 00:13:33
CPU Load
16%
System Name
VIVO-PER-27018750-AL
System Contact
System Location
FEIRA GRANDE - AL
ODU Serial Number
10480404020409040366000O
You are logged in as install (2)
© Copyright 2006-2014 STM Group. All Rights Reserved.
cmd - Atalho
Resposta de 8.8.8.8: bytes=32 tempo=1629ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=659ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1534ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=567ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=674ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1110ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=800ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=778ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1311ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=823ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1078ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=569ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1388ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=686ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1772ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1187ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=785ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1375ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=584ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1221ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=577ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1477ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=574ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=602ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=722ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=611ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=678ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=764ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=767ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=584ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=619ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=577ms TTL=44
Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 46, Recebidos = 45, Perdidos = 1 (2% perda),
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 560ms, Máximo = 2064ms, Média = 897ms
Control-C
^C
C:\Windows\System32>_
PT
19:56
25/06/2017