

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias Cliente: VIVO

Empresa
EMC BrasilVSAT-ID
VIVO-PER-23175354-CELink kbps
256/128Plataforma
VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode Popld Enable * 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055703 GHz Symbol Rate : 9.320056 Msps

S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 23 16APSK-9/10

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
Roll off : 0.25
SNR : 15.0 dB
Input Power : -28 dBm

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -15 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.7 dBm EIRP : 47.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)

IDU Output Power : -22.9 dBm

ODU Output Power : 33.6 dBm

EIRP : 46.9 dBW

Eb/No : 14.0 dB

Header Compression : Disabled

Timing correction : -106 us (260920 us)

Frequency correction: -330 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=1520 ms 64 bytes from 8.8.8.8: time=960 ms 64 bytes from 8.8.8.8: time=520 ms 64 bytes from 8.8.8.8: time=540 ms 64 bytes from 8.8.8.8: time=930 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 520/890/1520 ms