

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Cunha Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23011726-CE
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : max
EIRP : max

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -11.1 dBm

ODU Output Power : 34.2 dBm

EIRP : 47.5 dBW

Es/No : 13.0 dB

Header Compression : Disabled

Timing correction : -30 us (248966 us)

Frequency correction: -70 Hz

dvb rx show

Satellite (DVB) RX Configuration -----

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 25.333333 0 0.0 E 12.050000 DVB-S2 102

Yes

1 1 15.000000 12.059000 DVB-S2 4 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.050098 GHz

Symbol Rate : 25.333168 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 22 16APSK-8/9

: On Pilot Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS Roll off : 0.20 : 14.8 dB SNR : -26 dBm Input Power

