

# TERMO DE ACEITE TÉCNICO

**Solicitante:** VIVO- Projeto Escolas Rurais

**NOC/Operador:** Guilherme Henrique

**Cliente:** VIVO

**Empresa**  
EMC Brasil

**VSAT-ID**  
VIVO-PER-28006895-SE

**Link kbps**  
256k/128k

**Plataforma**  
VSAT



```
C:\Windows\system32\cmd.exe
#
Satellite (DUB) TX Configuration
Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 32.6 dBm
EIRP : 46.0 dBW
Default CW Frequency: 0.000000 GHz
ATH mode : UC-Max
Header Compression : None


Satellite (DUB) Transmitter Status
State : On (DUB-RCS2)
IDU Output Power : -19.2 dBm
ODU Output Power : 45.9 dBW
EIRP : 14.0 dB
Es/No : Disabled
Header Compression : Disabled
Timing correction : -64 us (250020 us)
Frequency correction : -90 Hz
#
Satellite (DUB) RX Configuration
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SybmRate[Mbps] Freq[GHz] Mode PopId SatId Pos SatName
Name Enable
0 0 25.333333 12.050000 DUB-S2 102 0 0.0 E
1 1 15.000000 12.050000 DUB-S2 4 0 0.0 E
* 6 6 25.333333 12.050000 DUB-S2 102 0 0.0 E
Yes
Yes

Satellite (DUB) Receiver Status
Rx State : On
DUB State : Forward link up
Network : 1326 T14R Beam
Frequency : 12.049900 GHz
Symbol Rate : 25.333267 Mbps
S2 ModCod :
- receiving : 22 16APSK-0/2
- current max : 20 16APSK-4/5
Pilot : On
Frame length : Short
DUB S2 Mode : ACM
DUB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 13.7 dB
Input Power : -24 dBm
#
```

SatLink VSAT

10.29.53.137/wmi/dwp/index\_page.dwp

 SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model	SatLink 2000
Software Version	16.0.1.57
LAN MAC Address	00:20:0e:10:56:34
DVB MAC Address	00:20:0e:10:56:34
System Up Time	0 days, 00:23:08
CPU Load	16%
System Name	VIVO-PER-28006895-SE
System Contact	
System Location	Campo do Brito - SE
ODU Serial Number	104804040203090307620000
ODU HW Version	4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

```
C:\Windows\system32\cmd.exe
Resposta de 8.8.8.8: bytes=32 tempo=2061ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=561ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=953ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1728ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2154ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2157ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2409ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1904ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1972ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1062ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2389ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1082ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2153ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1076ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=709ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=787ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=751ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=920ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=621ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=572ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=645ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=723ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=794ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=873ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=584ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=664ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=740ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=828ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=906ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=616ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=673ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=753ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=630ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1064ms TTL=44


Estatísticas do Ping para 8.8.8.8:
    Pacotes: Enviados = 88, Recebidos = 88, Perdidos = 0 (0% de perda).
    Aproximar um número redondo de vezes em milissegundos:
    Mínimo = 554ms, Máximo = 2706ms, Média = 1033ms
Control-C
C:\Users\DjTornados>arp -a

Interface: 10.29.53.138 --- 0xb
Endereço IP      Endereço físico      Tipo
10.29.53.137     00-20-0e-10-56-34   dinâmico
10.29.53.143     ff-ff-ff-ff-ff-ff   estático
224.0.0.2        01-00-5e-00-00-02   estático
224.0.0.251      01-00-5e-00-00-fb   estático
224.0.0.252      01-00-5e-00-00-fc   estático
224.0.1.60       01-00-5e-00-01-3e   estático
239.255.255.250  01-00-5e-7f-ff-fa   estático
255.255.255.255  ff-ff-ff-ff-ff-ff   estático

C:\Users\DjTornados>
```

SatLink VSAT

10.29.53.137/wmi/dwp/index\_page.dwp

 SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model	SatLink 2000
Software Version	16.0.1.57
LAN MAC Address	00:20:0e:10:56:34
DVB MAC Address	00:20:0e:10:56:34
System Up Time	0 days, 00:23:08
CPU Load	16%
System Name	VIVO-PER-28006895-SE
System Contact	
System Location	Campo do Brito - SE
ODU Serial Number	104804040203090307620000
ODU HW Version	4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.