


## TERMO DE ACEITE TÉCNICO


Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23061111-CE
 256k/128k
 VSAT





```
Satellite (DVB) RX Configuration
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
Name Enable * 0 0 9.320000
                          12.055825 DVB-S2 102 0 0.0 E
Yes
Satellite (DVB) Receiver Status
Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055912 GHz

Symbol Rate : 9.319958 Msps
S2 ModCod
  - receiving : 16 8PSK-8/9
      - current max : 16 8PSK-8/9
                 : On
Pilot
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 12.0 dB
Input Power : -28 dBm
IP DVB 10.50.1.147/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=590 ms
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=590 ms
64 bytes from 8.8.8.8: time=650 ms
64 bytes from 8.8.8.8: time=560 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
```

rtt min/avg/max = 560/590/650 ms