

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins Silva Cliente: VIVO

Empresa VSAT-ID

EMC Brasil VIVO-PER-26060361PE Link kbps 256/128 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -22 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 33.0 dBm

EIRP : 46.0 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -22.5 dBm
ODU Output Power : 33.0 dBm
EIRP : 46.0 dBW
Es/No : 13.0 dB
Header Compression : Disabled

Timing correction : -191 us (262284 us)

Frequency correction: -100 Hz

#

dvb rx show

Satellite (DVB) RX Configuration -----

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up Network : 1326, T14R Beam Frequency : 12.056063 GHz Symbol Rate : 9.320085 Msps

S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 16 8PSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off Roll off : 0.20 SNR : 14.4 dB Input Power : -26 dBm

