


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Renan Borges Sousa Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-31028789-MG
 256/128
 VSAT



#

Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.056036 GHz Symbol Rate : 9.319928 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 23 16APSK-9/10

Pilot : On
Frame length : Short

DVB S2 Mode : ACM

Roll off : 0.25

SNR : 14.2 dB

Input Power : -22 dBm

```
Satellite (DVB) TX Configuration
Auto start : Enabled IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : max
EIRP
                   : max
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State
                   : On (TDMA)
IDU Output Power : -20.0 dBm
ODU Output Power : 35.2 dBm
EIRP
                   : 48.5 dBW
                    : 14.0 dB
Eb/No
Header Compression : Disabled
Timing correction : -305 us (261644 us)
Frequency correction: -130 Hz
IP DVB 10.50.0.192/32
# ping 8.8.8.8
# 64 bytes from 8.8.8.8: time=730 ms
64 bytes from 8.8.8.8: time=720 ms
64 bytes from 8.8.8.8: time=600 ms
64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=610 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 600/650/730 ms
```