

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Alexandre Cruz Cliente: VIVO

Empresa VSAT-ID VIVO-PER-31159590-MG

Link kbps 256k/128k

Plataforma VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
EIRP : 47.0 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)

IDU Output Power : -26.5 dBm

ODU Output Power : 33.5 dBm

EIRP : 47.0 dBW

Es/No : 14.1 dB

Header Compression : Disabled

Timing correction : -114 us (262473 us)

Frequency correction: -310 Hz

dvb rx show

Satellite (DVB) RX Configuration ______

Auto start : Enabled
Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

: 15 minute RX watchdog

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status _____

Rx State

: On : Forward link up DVB State

: 1326, GlobalIP@Telstar-14R Network

Frequency : 12.055923 GHz Symbol Rate : 9.319996 Msps

S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 23 16APSK-9/10

: On Pilot Frame length : Short
DVB S2 Mode : ACM DVB S2 Mode : ACM Roll off : 0.25 SNR : 15.0 dB Input Power : -23 dBm

IP DVB 10.53.0.127/32

Ping desde o MGMT- Server ao IP de trafego e para o DVB.

Ping desde dentro da VSAT 8.8.8.8

ping 8.8.8.8

64 bytes from 8.8.8.8: time=2320 ms 64 bytes from 8.8.8.8: time=790 ms 64 bytes from 8.8.8.8: time=640 ms 64 bytes from 8.8.8.8: time=540 ms 64 bytes from 8.8.8.8: time=530 ms