

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-26084120-PE256/128VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 35.0 dBm
EIRP : 48.0 dBW
Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -15.2 dBm
ODU Output Power : 35.1 dBm
EIRP : 48.1 dBW
Es/No : 12.5 dB
Header Compression : Disabled

Timing correction : -169 us (262282 us)

Frequency correction: -190 Hz

dvb rx show

Satellite (DVB) RX Configuration _____

Auto start

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E

Yes

Satellite (DVB) Receiver Status _____

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.055435 GHz

Symbol Rate : 9.320008 Msps

S2 ModCod

- receiving : 13 8PSK-2/3 - current max : 15 8PSK-5/6

Pilot : On Frame length : Short DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 12.0 dB Input Power : -35 dBm

IP DVB 172.18.131.87/32