

# **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias Cliente: VIVO

> VSAT-ID Link kbps Plataforma Empresa **EMC** Brasil VIVO-PER-24062936-RN 256/128 **VSAT**



# Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable 12.055825 DVB-S2 4 \* 0 0 9.320000

### Satellite (DVB) Receiver Status

Rx State

: On

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

Frequency : 12.056401 GHz Symbol Rate : 9.320026 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 23 16APSK-9/10

Pilot : On

Frame length : Short DVB S2 Mode : ACM Roll off : 0.25 SNR : 14.2 dB Input Power : -26 dBm

# Satellite (DVB) TX Configuration

-----

Auto start : Enabled IDU Output Power : -15 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 33.7 dBm

EIRP : 47.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

#### Satellite (DVB) Transmitter Status

-----

State : On (TDMA)
IDU Output Power : -17.8 dBm
ODU Output Power : 34.4 dBm

EIRP : 47.7 dBW Eb/No : 15.5 dB

Header Compression: Disabled

Timing correction : -174 us (262399 us)

Frequency correction: 60 Hz

ping 8.8.8.8

64 bytes from 8.8.8.8: time=790 ms 64 bytes from 8.8.8.8: time=670 ms 64 bytes from 8.8.8.8: time=580 ms 64 bytes from 8.8.8.8: time=890 ms 64 bytes from 8.8.8.8: time=900 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 580/760/900 ms