


## TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-26184095-PE
 256k/128k
 VSAT



# dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 14.125500 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

```
_____
                  : On (DVB-RCS)
State
IDU Output Power : -19.9 dBm
                  : 13.0 dB
Es/No
Header Compression : Disabled
Timing correction : -167 us (260883 us)
Frequency correction: 100 Hz
# dvb rx show
Satellite (DVB) RX Configuration
-----
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
Auto start
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                            Name
Enable
         9.320000 12.055825 DVB-S2 102 0 0.0 E
* 0 0
Yes
Satellite (DVB) Receiver Status
          : On
: Forward link up
Rx State
DVB State
                  : 1326, GlobalIP@Telstar-14R
Network
Frequency : 12.055930 GHz
Symbol Rate : 9.320109 Msps
S2 ModCod
   - receiving : 16 8PSK-8/9
     - current max: 16 8PSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
                  : 14.3 dB
SNR
Input Power : -34 dBm
IP DVB 10.50.2.62/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=670 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=790 ms
64 bytes from 8.8.8.8: time=640 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 610/680/790 ms
```