

## **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Renan Borges Sousa Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-24052418-RN
 256/128
 VSAT



#

Satellite (DVB) RX Configuration
----Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
\* 0 0 9.320000 12.055825 DVB-S2 4 Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055687 GHz Symbol Rate : 9.319752 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 23 16APSK-9/10

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
Roll off : 0.25
SNR : 14.9 dB
Input Power : -30 dBm

```
Satellite (DVB) TX Configuration
______
Auto start : Enabled IDU Output Power : 0 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
                   : 47.0 dBW
EIRP
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)
IDU Output Power : -7.2 dBm
ODU Output Power : 36.0 dBm
EIRP
EIRP
                   : 49.3 dBW
Eb/No
                   : 16.0 dB
Header Compression : Disabled
Timing correction : 19 us (262220 us)
Frequency correction: -370 Hz
ping 8.8.8.8
64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=640 ms
64 bytes from 8.8.8.8: time=610 ms
64 bytes from 8.8.8.8: time=550 ms
64 bytes from 8.8.8.8: time=670 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 550/610/670 ms
```