


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira Cliente: Vivo

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-25019767-PB256K/128KVSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -20 dBm IDU Max Output Power: 0.0 dBm

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -19.8 dBm Es/No : 12.5 dB Header Compression : Disabled

Timing correction : -45 us (249080 us)

Frequency correction: 140 Hz

Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable * 0 30.000000 12.050000 DVB-S2 102 0.0 E Yes 25.333333 12.050000 DVB-S2 4 Ω 0.0 E 1 1

Yes

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050024 GHz
Symbol Rate : 30.000169 Msps

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 22 16APSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 15.3 dB
Input Power : -32 dBm

C:\Users\FAREIDNETO>ping 10.29.69.241

Disparando 10.29.69.241 com 32 bytes de dados:
Resposta de 10.29.69.241: bytes=32 tempo<1ms TTL=64

Estatísticas do Ping para 10.29.69.241:
Pacotes: Enviados = 4, Recebidos = 4, Perdidos = 0 (0% de perda),
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 0ms, Máximo = 0ms, Média = 0ms

C:\Users\FAREIDNETO>____