

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-35218959-SP256k/128kVSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.0 dBm
EIRP : 47.0 dBW
Default CW Frequency: 14.125850 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -22.4 dBm

ODU Output Power : 33.1 dBm

EIRP : 46.1 dBW

Es/No : 12.0 dB

Header Compression : Disabled

Timing correction : -77 us (255348 us)

Frequency correction: -10 Hz

dvb rx show

Satellite (DVB) RX Configuration ______

: Enabled Auto start

Max Traffic MODCOD : 23 16APSK-9/10 RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 15.000000 12.059000 DVB-S2 102 0 0.0 E

Yes

1 1 9.320000 12.055825 DVB-S2 4 0 0.0 E

Yes

Satellite (DVB) Receiver Status _____

Rx State : On

: Forward link up DVB State : 1326, T14R Beam Network : 12.058824 GHz : 15.000110 Frequency Symbol Rate : 15.000112 Msps

S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 22 16APSK-8/9

: On Pilot Frame length : Short DVB S2 Mode : ACM DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 15.1 dB : -26 dBm Input Power

