


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Renan Borges Sousa Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-26074869-PE
 256/128
 VSAT



#

Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
1 1 0.000000 0.000000 DVB-S2 0 No

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055869 GHz Symbol Rate : 9.319998 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 23 16APSK-9/10

Pilot : On
Frame length : Short

DVB S2 Mode : ACM
Roll off : 0.25
SNR : 14.9 dB

```
Input Power
                   : -22 dBm
Satellite (DVB) TX Configuration
Auto start : Enabled IDU Output Power : -21 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
EIRP
                    : 47.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
______
State
                    : On (TDMA)
IDU Output Power : -17.5 dBm
ODU Output Power : 33.5 dBm
EIRP
                    : 46.8 dBW
Eb/No
                    : 13.0 dB
\hbox{{\tt Header Compression}} \quad \hbox{: Disabled} \quad
Timing correction : -248 us (262291 us)
Frequency correction: -220 Hz
IP DVB 10.53.0.42/32
# ping 8.8.8.8
# 64 bytes from 8.8.8.8: time=530 ms
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=530 ms
64 bytes from 8.8.8.8: time=550 ms
64 bytes from 8.8.8.8: time=580 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 530/550/580 ms
```