

# TERMO DE ACEITE TÉCNICO

**Solicitante:** VIVO- Projeto Escolas Rurais

**NOC/Operador:** Leonardo Martins

**Cliente:** VIVO

**Empresa**  
EMC Brasil

**VSAT-ID**  
VIVO-PER-31177083-MG

**Link kbps**  
256k/128k

**Plataforma**  
VSAT



Internet Explorer - SatLink VSAT

10.47.9.217/vm/dsp/index\_page.dsp

STM SatLink VSAT

More visited: Primeiros passos, WhatsApp, Galeria do Web Site, Sites Sugeridos

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model: SatLink 2000

Software Version: 16.0.1.57

LAN MAC Address: 00:20:0e:10:60:2a

DVB MAC Address: 00:20:0e:10:60:2a

System Up Time: 0 days, 00:31:53

CPU Load: 20%

System Name: VIVO-PER-31177083-MG

System Contact:

System Location: GUAPE-MG

ODU Serial Number: 104804040203090404110000

ODU HW Version: 4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

quarta-feira, 31 de maio de 2017

10:51

Telnet 10.47.9.217

Satellite (DVB) Transmitter Status

State: On (DVB-RC32)

IMU Output Power: -16.6 dBm

ODU Output Power: 32.5 dBm

EIRP: 45.8 dBu

Ec/No: 13.8 dB

Header Compression: Disabled

Timing correction: -186 us (254938 us)

Frequency correction: 20 Hz

Satellite (DVB) RX Configuration

Auto start: Enabled

Max Traffic MODCOD: 23 16APSK-9/10

RX watchdog: 15 minute

Idx	Pri	SymbRate	Map	Freq	GHz	Mode	PopId	SatId	Pos	SatName
0	0	15.000000	Enable	12.059000	DVB-S2	102	0	0.0	E	
1	1	9.320000	Yes	12.055025	DVB-S2	4	0	0.0	E	

Satellite (DVB) Receiver Status

Re State: On

DVB State: Forward link up

Network: 1326, 114R Beam

Frequency: 12.058971 GHz

Symbol Rate: 14.999892 Mps

S2 ModCod: receiving: 18 16APSK-2/3, current max: 19 16APSK-3/4

Pilot: On

Frame length: Short

DVB S2 Mode: ACM

DVB S2 Stream type: MPEG-TS

Roll off: 0.30

SNR: 12.9 dB

Input Power: -25 dBm

Internet Explorer - SatLink VSAT

10.47.9.217/vm/dsp/index\_page.dsp

STM SatLink VSAT

More visited: Primeiros passos, WhatsApp, Galeria do Web Site, Sites Sugeridos, PQREI - Programa G..., Cobra Share: Acesso, Speed-Share: Entrada, TotalShare - Galaxy, UP World Torrents: Home

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model: SatLink 2000

Software Version: 16.0.1.57

LAN MAC Address: 00:20:0e:10:60:2a

DVB MAC Address: 00:20:0e:10:60:2a

System Up Time: 0 days, 00:31:53

CPU Load: 20%

System Name: VIVO-PER-31177083-MG

System Contact:

System Location: GUAPE-MG

ODU Serial Number: 104804040203090404110000

ODU HW Version: 4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

quarta-feira, 31 de maio de 2017

10:54

Prompt de comando

```

Resposta de 8.8.8.8: bytes=32 tempo=891ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=618ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=828ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=1818ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=1317ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=886ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=1887ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=538ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=511ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=789ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=796ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=1508ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=728ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=554ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=757ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=728ms TTL=55
Resposta de 8.8.8.8: bytes=32 tempo=1151ms TTL=55

Estatísticas do Ping para 8.8.8.8:
    Pacotes: Enviados = 79, Recebidos = 79, Perdidos = 0 (0% de perda).
    Aproximar um número redondo de vezes em milissegundos:
    Mínimo = 506ms, Máximo = 2036ms, Média = 898ms
    Control-C
    C:\Documents and Settings\Administrador>
  
```