


# TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogério Momi Frias Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-26026252-PE
 256/128
 VSAT



### Satellite (DVB) RX Configuration

-----

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name Enable

\* 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E Yes

Satellite (DVB) Receiver Status

-----

Rx State : On

DVB State : Forward link up

Network : 1326, GlobalIP@Telstar-14R

Frequency : 12.055793 GHz Symbol Rate : 9.319896 Msps

S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 16 8PSK-8/9

Pilot : On

Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 13.9 dB Input Power : -25 dBm

## Satellite (DVB) TX Configuration

-----

Auto start : Enabled IDU Output Power : -30 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 35.0 dBm

EIRP : 48.0 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

### Satellite (DVB) Transmitter Status

-----

State : On (DVB-RCS) IDU Output Power : -16.9 dBm ODU Output Power : 34.7 dBm

EIRP : 47.7 dBW Es/No : 13.0 dB

Header Compression: Disabled

Timing correction : -228 us (261620 us)

Frequency correction: -20 Hz

# ping 8.8.8.8

64 bytes from 8.8.8.8: time=1450 ms 64 bytes from 8.8.8.8: time=730 ms 64 bytes from 8.8.8.8: time=2010 ms 64 bytes from 8.8.8.8: time=780 ms 64 bytes from 8.8.8.8: time=700 ms

--- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 700/1130/2010 ms