

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-28004450-SE

Link kbps
256k/128k

Plataforma
VSAT



```
# dvb tx show
```

Satellite (DVB) TX Configuration

```
-----
Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 32.7 dBm
EIRP                 : 46.0 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
-----
State                : On (DVB-RCS2)
IDU Output Power     : -10.9 dBm
ODU Output Power     : 32.6 dBm
EIRP                 : 45.9 dBW
Es/No                : 11.5 dB
Header Compression   : Disabled
Timing correction     : -51 us (250778 us)
```

SetLink VSA7 Status Table:

Device Status	Model	SatLink 2000
Statistics	Software Version	16.0.1.57
Device	LAN MAC Address	00 20 0e 10 4b 0b
Eventlog	DVB MAC Address	00 20 0e 10 4b 0b
Configuration	System Up Time	0 days, 00:11:42
Satellite	CPU Load	31%
IP	System Name	VIVO-PER-28004450-SE
Static NAT	System Contact	
Lineup	System Location	Nossa senha aparecida /SE
Device	ODU Serial Number	10d404040203090207000000
Help	ODU HW Version	4.2
Introduction		
Status		
Configuration		

Configuration Page:

Statistics: Enviados = 59, Recebidos = 59, Perdidos = 0 (Bz de gerda).

Aproximar um número redondo de vezes em milissegundos:

Rinico = 570ms, Róximo = 2943ms, Média = 676ms

Control-C

C:\Users\Bjornados>arp -a

Interface: 10.29.54.170 --- Bah

Endereço IP	Endereço Físico	Tipo
10.29.54.169	00-20-0e-10-4b-0b	dinâmico
10.29.54.170	ff-ff-ff-ff-ff-ff	estático
224.0.0.2	01-00-5e-00-00-02	estático
224.0.0.254	01-00-5e-00-00-0b	estático
224.0.0.252	01-00-5e-00-00-04	estático
224.0.0.148	01-00-5e-00-00-03	estático
239.255.255.250	01-00-5e-7f-ff-fa	estático
255.255.255.255	ff-ff-ff-ff-ff-ff	estático

C:\Users\Bjornados>