


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos

Cliente: VIVO

Empresa VSAT-ID Link kbps Plataforma



```
_____
Auto start : Enabled IDU Output Power : -24 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
                  : 47.0 dBW
EIRP
Default CW Frequency: 14.125750 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
______
: On (TDMA)

IDU Output Power : -22.2 dBm

ODU Output Power : 33.5 dBm

EIRP
State
EIRP
                   : 46.8 dBW
Es/No
                   : 14.0 dB
Header Compression : Disabled
Timing correction : -217 us (260461 us)
Frequency correction: 20 Hz
# dvb rx show
Satellite (DVB) RX Configuration
Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 102 Yes
 4 4
         9.320000
                       12.055825 DVB-S2 4
                                                    No
Satellite (DVB) Receiver Status
______
Rx State : On

DVB State : Forward link up
Network
                  : 1326, GlobalIP@Telstar-14R
              : 12.055839 GHz
: 9.319904 Msps
Frequency
Symbol Rate
S2 ModCod
    - receiving : 16 8PSK-8/9
    - current max : 23 16APSK-9/10
Pilot : On Frame length : Short DVB S2 Mode : ACM
Frame Leng.
DVB S2 Mode
                  : ACM
Roll off
                  : 0.20
                  : 14.0 dB
Input Power : -20 dBm
IP DVB 10.50.0.9/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=760 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=520 ms
64 bytes from 8.8.8.8: time=590 ms
```

```
64 bytes from 8.8.8.8: time=510 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 510/590/760 ms
```