

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins Silva Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-25085662-PE
 256/128
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.5 dBm
EIRP : 48.0 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -13.8 dBm
ODU Output Power : 34.1 dBm
EIRP : 47.6 dBW
Es/No : 14.0 dB
Header Compression : Disabled

Timing correction : -181 us (262335 us)

Frequency correction: -150 Hz

dvb rx show

Satellite (DVB) RX Configuration

: Enabled Auto start

Max Traffic MODCOD : 23 16APSK-9/10 RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

9.320000 12.055825 DVB-S2 102 0 0.0 E * 0 0

Yes

Satellite (DVB) Receiver Status ______

Rx State : On

Rx State : On

DVB State : Forward link up

Network : 1326, T14R Beam

Frequency : 12.055979 GHz

Symbol Rate : 9.319949 Msps

S2 ModCod

- receiving : 14 8PSK-3/4 - current max : 16 8PSK-8/9

: On Pilot : Short Frame length : ACM DVB S2 Mode DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 13.6 dB : -35 dBm Input Power



