

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Henrique


Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-27018474-AL

Link kbps
256k/128k

Plataforma
VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
 IDU Output Power : -15 dBm
 IDU Max Output Power: 0.0 dBm
 ODU Output Power : 33.0 dBm
 EIRP : 46.0 dBW
 Default CW Frequency: 0.000000 GHz
 ATM mode : VC-Mux
 Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)
 IDU Output Power : -21.6 dBm
 ODU Output Power : 33.2 dBm
 EIRP : 46.2 dBW

Es/No : 8.5 dB
Header Compression : Disabled
Timing correction : 11 us (251015 us)
Frequency correction: -50 Hz
dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name	Enable
0	0	15.000000	12.059000	DVB-S2 102	0	0.0	E		Yes	
1	1	9.320000	12.055825	DVB-S2 4	0	0.0	E		Yes	
* 6	6	25.333333	12.050000	DVB-S2 102	0	0.0	E		Yes	
7	7	30.000000	12.050000	DVB-S2 102	0	0.0	E		Yes	

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050103 GHz
Symbol Rate : 25.333163 Msps
S2 ModCod
- receiving : 20 16APSK-4/5
- current max : 20 16APSK-4/5
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 13.9 dB
Input Power : -28 dBm

SpeedOf.Me, HTML5 Spe x

SatLink VSAT x

10.29.47.9/wmi/dwp/index_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

ODU Serial Number

ODU HW Version

SatLink 2000

16.0.1.57

00:20:0e:10:51:bf

00:20:0e:10:51:bf

0 days, 00:14:49

13%

VIVO-PER-27018474-AL

Feira grande - AL

104804040203090704860000

4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

cmd - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=580ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=583ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=565ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=575ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2070ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=783ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=614ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=599ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=562ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=588ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=590ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=614ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=568ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=585ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=615ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=580ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=651ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=618ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=560ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=644ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=564ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=607ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=609ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=676ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=630ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=567ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=669ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=599ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=600ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=574ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=598ms TTL=44

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 51, Recebidos = 51, Perdidos = 0 (0% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 562ms, Máximo = 2070ms, Média = 640ms
Control-C
C:\Windows\System32>arp -a

Interface: 10.29.47.10 --- 0xb
Endereço IP Endereço físico Tipo
10.29.47.9 00-20-0e-10-51-bf dinâmico
10.29.47.15 ff-ff-ff-ff-ff-ff estático
224.0.0.2 01-00-5e-00-00-02 estático
224.0.0.22 01-00-5e-00-00-16 estático
224.0.0.251 01-00-5e-00-00-fb estático
224.0.0.252 01-00-5e-00-00-fc estático
224.0.0.253 01-00-5e-00-00-fd estático
226.178.217.5 01-00-5e-32-d9-05 estático
239.192.152.143 01-00-5e-40-98-8f estático
239.255.255.250 01-00-5e-7f-ff-fa estático
255.255.255.255 ff-ff-ff-ff-ff-ff estático

C:\Windows\System32>