

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira


Cliente: Vivo

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-26090163-PE

Link kbps
256K/128K

Plataforma
VSAT



dvb tx show

Satellite (DVB) TX Configuration

```
Auto start           : Enabled
IDU Output Power     : -21 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.7 dBm
EIRP                 : 47.0 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
State                : On (DVB-RCS2)
IDU Output Power     : -17.0 dBm
ODU Output Power     : 33.5 dBm
EIRP                 : 46.8 dBW
Es/No                : 13.0 dB
Header Compression   : Disabled
```

Timing correction : -80 us (251320 us)
Frequency correction: -30 Hz

dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msp/s]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.049991 GHz
Symbol Rate : 25.333176 Msp/s
S2 ModCod
- receiving : 12 8PSK-3/5
- current max : 22 16APSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 15.5 dB
Input Power : -19 dBm

SatLink VSAT

10.29.58.169/wmi/dwp/index_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

ODU Serial Number

ODU HW Version

SatLink 2000

16.0.1.57

00:20:0e:10:55:58

00:20:0e:10:55:58

0 days, 00:05:03

21%

VIVO-PER-26090163-PE

Lagoa do Carro - PE

104804040204090403410000

4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

CMD - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=814ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=883ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=965ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=699ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=752ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=832ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=911ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=742ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=711ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=772ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=875ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=933ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=1030ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=701ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=779ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=854ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=1301ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=718ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=725ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=873ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=2133ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=1357ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=671ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=739ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=854ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=885ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=959ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=604ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=1853ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=677ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=859ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=943ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=1021ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=715ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=668ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=862ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=952ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=1427ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=716ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=742ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=827ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=922ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=983ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=1060ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=728ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=681ms TTL=40
Resposta de 8.8.8.8: bytes=32 tempo=878ms TTL=40

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 81, Recebidos = 1 (1% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 658ms, Máximo = 2452ms, Média = 965ms
Control-C
^C
C:\Windows\System32>

10:00

15/08/2017