Dvb tx show



TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Leonardo Martins Silva Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-25085247-PE
 256/128
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -30 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : 34.5 dBm EIRP : 48.0 dBW Default CW Frequency: 0.000000 GHz ATM mode : VC-Mux

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)

IDU Output Power : -18.7 dBm

ODU Output Power : 30.7 dBm

EIRP : 44.2 dBW

Es/No : 13.0 dB

Header Compression : Disabled

Header Compression : Disabled
Timing correction : -128 us (262277 us)

Frequency correction: -40 Hz

#

dvb rx show

Satellite (DVB) RX Configuration

______ : Enabled Auto start

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

9.320000 12.055825 DVB-S2 102 0 0.0 E * 0 0

Yes

Satellite (DVB) Receiver Status _____

Rx State

: On : Forward link up : 1326, T14R Beam DVB State Network : 12.056003 GHz : 9.320149 Msps Frequency Symbol Rate

S2 ModCod

- receiving : 15 8PSK-5/6 - current max : 15 8PSK-5/6

: On Pilot Frame length : Short
DVB S2 Mode : ACM : ACM DVB S2 Mode DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 12.0 dB Input Power : -26 dBm

