


# **TERMO DE ACEITE TÉCNICO**

Solicitante: VIVO- Projeto Escolas Rurais

Cliente: VIVO NOC/Operador: Rogério Momi Frias

> **Empresa** VSAT-ID Link kbps Plataforma **EMC** Brasil VIVO-PER-31047252-MG 256/128 **VSAT**



# Satellite (DVB) RX Configuration

Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName

\* 0 0 9.320000 12.055825 DVB-S2 102 0 0.0 E Name Enable Yes

#### Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

Frequency : 12.056202 GHz Symbol Rate : 9.320018 Msps

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 16 8PSK-8/9

Pilot : On Frame length : Short DVB S2 Mode : ACM

DVB S2 Stream type: MPEG-TS

Roll off : 0.20 SNR : 13.6 dB Input Power : -28 dBm

# Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm

EIRP : 48.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

# Satellite (DVB) Transmitter Status

-----

State : On (DVB-RCS)
IDU Output Power : -22.8 dBm
ODU Output Power : 34.6 dBm

EIRP : 47.9 dBW Es/No : 14.0 dB

Header Compression: Disabled

Timing correction: -329 us (262439 us)

Frequency correction: 120 Hz

# ping 8.8.8.8

64 bytes from 8.8.8.8: time=660 ms 64 bytes from 8.8.8.8: time=710 ms 64 bytes from 8.8.8.8: time=710 ms 64 bytes from 8.8.8.8: time=710 ms 64 bytes from 8.8.8.8: time=720 ms

# --- ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 660/700/720 ms