


TERMO DE ACEITE TÉCNICO

Solicitante: PRODEMGE / SEE

NOC/Operadora: Paulo de Tarso Operadora/Cliente: João Gustavo F M Sobrinho

GRE/Prodemge: João Antinossi Responsável/cliente: Ivonildes Alves C Gusmao

> VSAT-ID Porta kbps Plataforma Consórcio EMC/Vodanet **VSAT** SEE-JABA-21941 2Mbps



PRINTS Traine Grapher VII.20 Not - WWW.SWIF NOTICE

Satellite (DVB) RX Configuration Auto start : Enabled

Max Traffic MODCOD : 23 16APSK-9/10 RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName

Name Enable

* 0 0 4.883300 12.176420 DVB-S2 104 0 0.0 E

Yes

Satellite (DVB) Receiver Status _____

Rx State : On

DVB State : Forward link up

Network

: 65281, Prodemge@Vodanet : 12.176507 GHz : 4.882962 Msps Frequency Symbol Rate

S2 ModCod

- receiving : 4 QPSK-1/2 - current max : 16 8PSK-8/9

Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Starrage DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 16.4 dB Input Power : -36 dBm

```
Satellite (DVB) TX Configuration
Auto start : Enabled IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
                  : 33.2 dBm
ODU Output Power
EIRP
                    : 46.5 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : UDP/IP
Satellite (DVB) Transmitter Status
                   : On (DVB-RCS2)
State
IDU Output Power : -14.4 dBm
ODU Output Power : 33.2 dBm
EIRP
                   : 46.5 dBW
Es/No
                     : 14.0 dB
Header Compression : Disabled - HC for RCS2 not supported by HUB Timing correction : -331 us (280998 us)
Frequency correction: 110 Hz
System Information:
                        : SEE-JABA-21941
    Name
    Location
                         : Janaúba
    Contact
    System Up time
                       : 0 days, 00:28:48
                       : 11%
    CPU Load
    System time(UTC)
                         : 16 October 2017 14:58:39
    Broadcast Message : not set
HW:
    Model
                        : SatLink 2000
                        : 120033
    HW ID
    Main board ID : 120026 R6.2
MAC addresses:
    Ethernet (LAN) : 00:20:0e:10:55:1b
Satellite (DVB) : 00:20:0e:10:55:1b
arp show
   NetAddr State MacAddr
                                              Τf
   10.212.29.2 Dynamic b4:99:ba:00:92:6b 1
Pinging 10.212.29.1 with 32 bytes of data:
Reply from 10.212.29.1: bytes=32 time=559ms TTL=56
Reply from 10.212.29.1: bytes=32 time=557ms TTL=56
Reply from 10.212.29.1: bytes=32 time=519ms TTL=56
Reply from 10.212.29.1: bytes=32 time=554ms TTL=56
Reply from 10.212.29.1: bytes=32 time=567ms \mathtt{TTL}=56
Reply from 10.212.29.1: bytes=32 time=564ms TTL=56
Reply from 10.212.29.1: bytes=32 time=562ms TTL=56
Reply from 10.212.29.1: bytes=32 time=549ms TTL=56
Reply from 10.212.29.1: bytes=32 time=563ms TTL=56
Reply from 10.212.29.1: bytes=32 time=573ms TTL=56
Ping statistics for 10.212.29.1:
   Packets: Sent = 10, Received = 10, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
   Minimum = 519ms, Maximum = 573ms, Average = 556ms
```

Lista de sites acessados:
www.globo.com – ok
www.hotmail.com – ok
www.google.com – ok
www.educacao.mg.gov.br – ok
Responsável pelo teste de navegação:
Nome: Ivonildes Alves C Gusmao
Função: Diretora MASP: 345742-1
Telefone: (38) 3821-1607
Horário de funcionamento da escola: 07:00 as 18:00