

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Renan Borges Sousa Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-26073919-PE256k/128kVSAT



dvb tx show

#

Satellite (DVB) TX Configuration

Auto start : Enabled IDU Output Power : -30 dBm IDU Max Output Power: 0.0 dBm ODU Output Power : max EIRP : max

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -15.6 dBm
ODU Output Power : 35.0 dBm
EIRP : 48.0 dBW
Es/No : 12.0 dB
Header Compression : Disabled

Timing correction : -208 us (262091 us)

Frequency correction: -80 Hz

#

```
# dvb rx show
Satellite (DVB) RX Configuration
_____
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
                  : 15 minute
RX watchdog
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos
                                                      SatName
             Enable
Name
                      12.055825 DVB-S2 102 0 0.0 E
* 0 0
         9.320000
              Yes
Satellite (DVB) Receiver Status
Rx State
                 : On
DVB State
                : Forward link up
                : 1326, GlobalIP@Telstar-14R
Network
Symbol Rate : 9 320001
S2 ModCod
  - receiving : 1 QPSK-1/4
    - current max : 16 8PSK-8/9
             : On
Pilot
Frame length : Short DVB S2 Mode : ACM
DVB S2 Mode
                 : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 14.1 dB
Input Power : -20 dBm
IP DVB 10.50.2.63/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
C:\Documents and Settings\Administrator.DVB-RCS>ping 172.18.128.192
Pinging 172.18.128.192 with 32 bytes of data:
Reply from 172.18.128.192: bytes=32 time=1915ms TTL=62
Reply from 172.18.128.192: bytes=32 time=635ms TTL=62
Reply from 172.18.128.192: bytes=32 time=555ms TTL=62
Reply from 172.18.128.192: bytes=32 time=580ms TTL=62
Ping statistics for 172.18.128.192:
   Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
   Minimum = 555ms, Maximum = 1915ms, Average = 921ms
Ping desde dentro da VSAT 8.8.8.8
# 64 bytes from 8.8.8.8: time=670 ms
64 bytes from 8.8.8.8: time=700 ms
64 bytes from 8.8.8.8: time=720 ms
64 bytes from 8.8.8.8: time=740 ms
64 bytes from 8.8.8.8: time=700 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 670/700/740 ms
```