

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias Cliente: VIVO

> **Empresa** VSAT-ID **EMC** Brasil VIVO-PER-31086274-MG

Link kbps 256/128

Plataforma VSAT



Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable * 0 0 9.320000 12.055825 DVB-S2 4

Satellite (DVB) Receiver Status

Rx State : On

DVB State

: Forward link up

: 1326, GlobalIP@Telstar-14R Network

Frequency : 12.055690 GHz Symbol Rate : 9.319883 Msps

S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 23 16APSK-9/10

Pilot : On Frame length : Short DVB S2 Mode : ACM : 0.25 Roll off

: 14.9 dB SNR Input Power : -17 dBm

```
Satellite (DVB) TX Configuration
-----
Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm
EIRP
            : 48.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression: None
Satellite (DVB) Transmitter Status
            : On (TDMA)
IDU Output Power : -19.5 dBm
ODU Output Power : 35.1 dBm
EIRP
             : 48.4 dBW
Eb/No
              : 16.0 dB
Header Compression: Disabled
Timing correction : -142 us (261090 us)
Frequency correction: -390 Hz
Pinging 10.53.1.14 with 32 bytes of data:
Reply from 10.53.1.14: bytes=32 time=519ms TTL=61
Reply from 10.53.1.14: bytes=32 time=625ms TTL=61
Reply from 10.53.1.14: bytes=32 time=546ms TTL=61
Reply from 10.53.1.14: bytes=32 time=657ms TTL=61
Ping statistics for 10.53.1.14:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
  Minimum = 519ms, Maximum = 657ms, Average = 586ms
Pinging 10.29.6.1 with 32 bytes of data:
Reply from 10.29.6.1: bytes=32 time=1449ms TTL=61
Reply from 10.29.6.1: bytes=32 time=527ms TTL=61
Reply from 10.29.6.1: bytes=32 time=1187ms TTL=61
Reply from 10.29.6.1: bytes=32 time=1012ms TTL=61
Ping statistics for 10.29.6.1:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
  Minimum = 527ms, Maximum = 1449ms, Average = 1043ms
ping 8.8.8.8
64 bytes from 8.8.8.8: time=2640 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=540 ms
64 bytes from 8.8.8.8: time=540 ms
64 bytes from 8.8.8.8: time=560 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
```

rtt min/avg/max = 540/970/2640 ms