

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-27032639-AL
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 34.7 dBm
EIRP : 48.0 dBW
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (TDMA)

IDU Output Power : -24.0 dBm

ODU Output Power : 32.8 dBm

EIRP : 46.1 dBW

Eb/No : 14.0 dB

```
Header Compression : Disabled
Timing correction : -308 us (262614 us)
Frequency correction: -150 Hz
# dvb rx show
Satellite (DVB) RX Configuration
______
Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
Satellite (DVB) Receiver Status
_____
             : On: Forward link up: 1326, GlobalIP@Telstar-14R
Rx State
DVB State
              : 12.055951 GHz
: 9 310010
Network
Frequency
Symbol Rate
S2 ModCod
     - receiving : 1 QPSK-1/4
- current max : 23 16APSK-9/10
              : On
Pilot
Frame length
                   : Short
DVB S2 Mode
                   : ACM
Roll off
                   : 0.25
                   : 15.3 dB
SNR
Input Power : -24 dBm
IP DVB 10.50.0.117/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=870 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=580 ms
64 bytes from 8.8.8.8: time=680 ms
64 bytes from 8.8.8.8: time=780 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
```

rtt min/avg/max = 580/690/870 ms