

TERMO DE ACEITE TÉCNICO

Plataforma

VSAT

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Rogerio Momi Frias Cliente: VIVO

> **Empresa** VSAT-ID Link kbps **EMC** Brasil VIVO-PER-31086711-MG 256/128



Satellite (DVB) RX Configuration

Auto start : Enabled

Max MODCOD : 23 16APSK-9/10 (SNR threshold: 23.5 dB)

: 15 minute RX watchdog

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable Yes

* 0 0 9.320000 12.055825 DVB-S2 4 1 1 0.000000 0.000000 DVB-S2 2 No

Satellite (DVB) Receiver Status

Rx State : On

DVB State : Forward link up

: 1326, GlobalIP@Telstar-14R Network

Frequency : 12.055635 GHz Symbol Rate : 9.319974 Msps S2 ModCod

- receiving : 16 8PSK-8/9 - current max : 23 16APSK-9/10

Pilot : On : Short Frame length

DVB S2 Mode : ACM Roll off : 0.25 SNR : 15.1 dB : -25 dBm Input Power

```
Satellite (DVB) TX Configuration
-----
Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
EIRP
            : 47.0 dBW
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression: None
Satellite (DVB) Transmitter Status
State : On (TDMA)
IDU Output Power : -21.3 dBm
ODU Output Power : 34.3 dBm
           : 47.6 dBW
EIRP
Eb/No
             : 14.0 dB
Header Compression: Disabled
Timing correction: 10 us (260937 us)
Frequency correction: -400 Hz
Pinging 10.53.0.229 with 32 bytes of data:
Reply from 10.53.0.229: bytes=32 time=1941ms TTL=61
Reply from 10.53.0.229: bytes=32 time=1298ms TTL=61
Reply from 10.53.0.229: bytes=32 time=914ms TTL=61
Reply from 10.53.0.229: bytes=32 time=835ms TTL=61
Ping statistics for 10.53.0.229:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
  Minimum = 835ms, Maximum = 1941ms, Average = 1247ms
Pinging 10.29.4.201 with 32 bytes of data:
Reply from 10.29.4.201; bytes=32 time=1901ms TTL=61
Reply from 10.29.4.201: bytes=32 time=737ms TTL=61
Reply from 10.29.4.201: bytes=32 time=662ms TTL=61
Reply from 10.29.4.201: bytes=32 time=587ms TTL=61
Ping statistics for 10.29.4.201:
  Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
  Minimum = 587ms, Maximum = 1901ms, Average = 971ms
ping 8.8.8.8
64 bytes from 8.8.8.8: time=950 ms
```

64 bytes from 8.8.8.8: time=950 ms 64 bytes from 8.8.8.8: time=1470 ms 64 bytes from 8.8.8.8: time=570 ms 64 bytes from 8.8.8.8: time=900 ms 64 bytes from 8.8.8.8: time=560 ms

--- 8.8.8.8 ping statistics ---

5 packets transmitted, 5 received, 0.00 percent packet loss rtt min/avg/max = 560/880/1470 ms