

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Wallace Teixeira


Cliente: Vivo

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-26102013-PE

Link kbps
256K/128K

Plataforma
VSAT



```
# dvb tx show
```

Satellite (DVB) TX Configuration

```
-----
Auto start           : Enabled
IDU Output Power     : -20 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.7 dBm
EIRP                 : 47.0 dBW
Default CW Frequency : 0.000000 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
-----
State                : On (DVB-RCS2)
IDU Output Power     : -15.4 dBm
ODU Output Power     : 33.1 dBm
EIRP                 : 46.4 dBW
Es/No                : 14.0 dB
```

Header Compression : Disabled
Timing correction : -78 us (251323 us)
Frequency correction: -70 Hz
dvb rx show

Satellite (DVB) RX Configuration

Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx	Pri	SymbRate[Msp/s]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName
Name		Enable						
* 0	0	25.333333	12.050000	DVB-S2	102	0	0.0 E	
Yes								
7	7	30.000000	12.050000	DVB-S2	102	0	0.0 E	
Yes								

Satellite (DVB) Receiver Status

Rx State : On
DVB State : Forward link up
Network : 1326, T14R Beam
Frequency : 12.050007 GHz
Symbol Rate : 25.333083 Msp/s
S2 ModCod
- receiving : 7 QPSK-3/4
- current max : 22 16APSK-8/9
Pilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
SNR : 15.0 dB
Input Power : -21 dBm

SatLink VSAT

10.29.58.17/wmi/dwp/index_page.dwp

STM

SatLink VSAT

Status

Satellite

Statistics

Device

DHCP

Eventlog

Configuration

Satellite

IP

Static NAT

Lineup

Device

Help

Introduction

Status

Configuration

Device Status

Model

Software Version

LAN MAC Address

DVB MAC Address

System Up Time

CPU Load

System Name

System Contact

System Location

ODU Serial Number

ODU HW Version

SatLink 2000

16.0.1.57

00:20:0e:10:60:df

00:20:0e:10:60:df

0 days, 00:08:36

25%

VIVO-PER-26102013-PE

Primavera - PE

104804040204090305590000

4.2

You are logged in as install (2)

© Copyright 2006-2014 STM Group. All Rights Reserved.

CMD - Atalho

Resposta de 8.8.8.8: bytes=32 tempo=1498ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1362ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=381ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=272ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=742ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=644ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1123ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1188ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=595ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1556ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=151ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=703ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=609ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=601ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=153ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=996ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1033ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1111ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=576ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1190ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=3337ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2281ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2696ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=965ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=3243ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=2621ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=503ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1167ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1543ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=611ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=931ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=827ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1892ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=704ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1222ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1443ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=721ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1493ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1068ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1076ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1071ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1437ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=730ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=749ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=819ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1615ms TTL=44
Resposta de 8.8.8.8: bytes=32 tempo=1063ms TTL=44

Estatísticas do Ping para 8.8.8.8:
Pacotes: Enviados = 123, Recebidos = 0 (0% de perda).
Aproximar um número redondo de vezes em milissegundos:
Mínimo = 555ms, Máximo = 3562ms, Média = 1038ms
Control-C
^C
C:\Windows\System32>

PT

13:11

12/08/2017