

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá

Cliente: VIVO

Empresa
EMC Brasil

VSAT-ID
VIVO-PER-25077058-PB

Link kbps
256/128

Plataforma
VSAT



dvb tx show

Satellite (DVB) TX Configuration

```
Auto start           : Enabled
IDU Output Power     : -30 dBm
IDU Max Output Power : 0.0 dBm
ODU Output Power     : 33.7 dBm
EIRP                 : 47.0 dBW
Default CW Frequency: 14.125850 GHz
ATM mode             : VC-Mux
Header Compression   : None
```

Satellite (DVB) Transmitter Status

```
State                : On (DVB-RCS)
IDU Output Power     : -22.1 dBm
ODU Output Power     : 33.6 dBm
EIRP                 : 46.9 dBW
Es/No                : 14.0 dB
Header Compression   : Disabled
Timing correction    : -269 us (262170 us)
Frequency correction : -30 Hz
```

dvb rx show

Satellite (DVB) RX Configuration

```
-----
Auto start           : Enabled
Max Traffic MODCOD   : 23   16APSK-9/10
RX watchdog          : 15 minute
```

Idx	Pri	SymbRate[Mbps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name
Enable									
* 0	0	9.320000	12.055825	DVB-S2	102	0	0.0 E		
Yes									

Satellite (DVB) Receiver Status

```
-----
Rx State             : On
DVB State            : Forward link up
Network              : 1326, GlobalIP@Telstar-14R
Frequency            : 12.055976 GHz
Symbol Rate          : 9.320034 Msps
S2 ModCod
- receiving          : 13   8PSK-2/3
- current max        : 16   8PSK-8/9
Pilot                : On
Frame length         : Short
DVB S2 Mode          : ACM
DVB S2 Stream type   : MPEG-TS
Roll off             : 0.20
SNR                  : 14.2 dB
Input Power          : -27 dBm
```

```
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=640 ms
64 bytes from 8.8.8.8: time=630 ms
64 bytes from 8.8.8.8: time=990 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=970 ms
```

```
--- ping statistics ---
5 packets transmitted, 4 received, 20.00 percent packet loss
rtt min/avg/max = 630/740/990 ms
#
```



