

TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Bruno Carvalho de Sá Cliente: VIVO

EmpresaVSAT-IDLink kbpsPlataformaEMC BrasilVIVO-PER-26155249-PE256/128VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -30 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 35.0 dBm
EIRP : 48.0 dBW

Default CW Frequency: 14.125750 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS)
IDU Output Power : -20.0 dBm
ODU Output Power : 35.2 dBm
EIRP : 48.2 dBW
Es/No : 14.0 dB
Header Compression : Disabled

Timing correction : -129 us (262085 us)

Frequency correction: 60 Hz

```
# dvb rx show
Satellite (DVB) RX Configuration
-----
Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName
                                                                            Name
Enable
         9.320000 12.055825 DVB-S2 102 0 0.0 E
* 0 0
Yes
Satellite (DVB) Receiver Status
           : On
: Forward link up
Rx State
DVB State
                  : 1326, GlobalIP@Telstar-14R
Network
             : 12.055917 GHz
Frequency
Symbol Rate
                  : 9.319918 Msps
S2 ModCod
  - receiving : 14 8PSK-3/4
     - current max : 16
             : On
Pilot
Frame length : Short DVB S2 Mode : ACM
                  : ACM
DVB S2 Stream type : MPEG-TS
Roll off : 0.20
                  : 13.9 dB
SNR
Input Power
                  : -29 dBm
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=600 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=720 ms
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=720 ms
--- ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 600/690/720 ms
```

