


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Allan Santos Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-25034065-PB
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled

IDU Output Power : -23 dBm

IDU Max Output Power: 0.0 dBm

ODU Output Power : 33.7 dBm

EIRP : 47.0 dBW

Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

```
Satellite (DVB) Transmitter Status
______
State
                   : On (TDMA)
IDU Output Power : -17.2 dBm
ODU Output Power : 33.6 dBm
                   : 46.9 dBW
EIRP
                   : 15.0 dB
Eb/No
Header Compression : Disabled
Timing correction : -73 us (261726 us)
Frequency correction: -410 Hz
# dvb rx show
Satellite (DVB) RX Configuration
_____
Auto start : Enabled Max MODCOD : 23 160
                  : 23 16APSK-9/10 (SNR threshold: 23.5 dB) 
: 15 minute
RX watchdog
Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable
* 0 0 9.320000 12.055825 DVB-S2 4 Yes
Satellite (DVB) Receiver Status
Rx State : On

DVB State : Forward link up
                  : 1326, GlobalIP@Telstar-14R
Network
              : 12.055437 GHz
: 9.319902 Msps
Frequency
Symbol Rate
S2 ModCod
   - receiving : 14 8PSK-3/4
     - current max : 23 16APSK-9/10
Pilot : On
Frame length : Short
DVB S2 Mode · ACM
DVB S2 Mode
                  : ACM
Roll off
                  : 0.25
SNR
                  : 14.7 dB
Input Power : -27 dBm
IP DVB 10.50.0.28/32
Ping desde o MGMT- Server ao IP de trafego e para o DVB.
Ping desde dentro da VSAT 8.8.8.8
# ping 8.8.8.8
64 bytes from 8.8.8.8: time=710 ms
64 bytes from 8.8.8.8: time=570 ms
64 bytes from 8.8.8.8: time=530 ms
64 bytes from 8.8.8.8: time=1290 ms
64 bytes from 8.8.8.8: time=550 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
```

rtt min/avg/max = 530/720/1290 ms