


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

Cliente: VIVO NOC/Operador: Renan Borges Sousa

> **Empresa** VSAT-ID Link kbps Plataforma EMC Brasil VIVO-PER-23006170-CE 256/128 **VSAT**



Satellite (DVB) RX Configuration

Auto start : Enabled

: 23 16APSK-9/10 (SNR threshold: 23.5 dB) Max MODCOD

: 15 minute RX watchdog

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId Enable 9.320000 12.055825 DVB-S2 4 * 0 0 Yes

Satellite (DVB) Receiver Status ______

Rx State : On

: Forward link up DVB State

: 1326, GlobalIP@Telstar-14R Network

: 12.055581 GHz Frequency : 9.319881 Msps Symbol Rate

S2 ModCod

- receiving : 1 QPSK-1/4 - current max : 15 8PSK-5/6

Pilot : On Frame length : Short DVB S2 Mode : ACM : 0.25 Roll off SNR : 12.6 dB Input Power : -27 dBm

```
Satellite (DVB) TX Configuration
-----
Auto start : Enabled IDU Output Power : -15 dBm
IDU Max Output Power: 0.0 dBm
ODU Output Power : 33.7 dBm
                   : 47.0 dBW
EIRP
Default CW Frequency: 0.000000 GHz
ATM mode : VC-Mux
Header Compression : None
Satellite (DVB) Transmitter Status
_____
State : On (TDMA)

IDU Output Power : -25.3 dBm

ODU Output Power : 33.8 dBm

EIRP
Eb/No
                    : 11.5 dB
Header Compression : Disabled
Timing correction : -227 us (260459 us)
Frequency correction: -100 Hz
IP DVB 10.50.0.60/32
#ping 8.8.8.8
# 64 bytes from 8.8.8.8: time=1320 ms
64 bytes from 8.8.8.8: time=910 ms
64 bytes from 8.8.8.8: time=910 ms
64 bytes from 8.8.8.8: time=920 ms
64 bytes from 8.8.8.8: time=930 ms
--- 8.8.8.8 ping statistics ---
5 packets transmitted, 5 received, 0.00 percent packet loss
rtt min/avg/max = 910/990/1320 ms
```