


TERMO DE ACEITE TÉCNICO

Solicitante: VIVO- Projeto Escolas Rurais

NOC/Operador: Guilherme Henrique Cliente: VIVO

 Empresa
 VSAT-ID
 Link kbps
 Plataforma

 EMC Brasil
 VIVO-PER-23141700-CE
 256k/128k
 VSAT



dvb tx show

Satellite (DVB) TX Configuration

Auto start : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz

ATM mode : VC-Mux Header Compression : None

Satellite (DVB) Transmitter Status

State : On (DVB-RCS2)

IDU Output Power : -20.2 dBm

Es/No : 17.0 dB

Header Compression : Disabled

Timing correction : -134 us (254414 us)

Frequency correction: -40 Hz

dvb rx show

Satellite (DVB) RX Configuration -----Auto start : Enabled
Max Traffic MODCOD : 23 16APSK-9/10
RX watchdog : 15 minute

Idx Pri SymbRate[Msps] Freq[GHz] Mode PopId SatId Pos SatName Name

Enable

* 0 0 15.000000 0 0.0 E 12.059000 DVB-S2 102

Yes

1 1 9.320000 12.055825 DVB-S2 4 0 0.0 E

Yes

Satellite (DVB) Receiver Status -----

Rx State : On
DVB State : Forward link up : 1326, T14R Beam Network Frequency : 12.059138 GHz Symbol Rate : 15.000327 Msps

S2 ModCod

- receiving : 18 16APSK-2/3 - current max : 22 16APSK-8/9

rilot : On
Frame length : Short
DVB S2 Mode : ACM
DVB S2 Stroom DVB S2 Stream type : MPEG-TS Roll off : 0.20 SNR : 14.5 dB Input Power : -34 dBm

23141700