



TERMO DE ACEITE TÉCNICO

Solicitante: ATI - Agência de Tecnologia da Informação do Estado do Piauí

NOC/Operadora: Jefferson Marques

Técnico Instalador: Jean Polini

Contato: 11 97701-2709

Email: jeanpolinitelecom@gmail.com


ATI: Wesley Souza

Responsável/cliente: Carla Patricia de Sousa

Orgão: SEDUC	Unidade: Seduc – Vazea Grande PI	Data Instalação 18/09/2018	Data Ativação 20/09/2018
Operadora Global Eagle	VSAT-ID ATI-ES-0047-IND	Porta kbps 4096/512	Tipo Indoor

Piauí, 20 de setembro de 2018

1 – Local da Instalação



2 – Configurações do Modem

device show

System Information:

Name : ATI-ES-0047-IND
 Location : VARZEA GRANDE PI
 Contact :
 System Up time : 0 days, 00:50:19
 CPU Load : 34%
 System time(UTC) : 20 September 2018 14:01:02
 Broadcast Message : not set

HW:

Model : SatLink 2000
 HW ID : 120033
 Main board ID : 120026 R6.2

MAC addresses:

Ethernet (LAN) : 00:20:0e:10:8c:c3
 Satellite (DVB) : 00:20:0e:10:8c:c3

dvb tx show

Satellite (DVB) TX Configuration

 Auto start : Enabled
 IDU Output Power : -20 dBm
 IDU Max Output Power: 0.0 dBm
 Default CW Frequency: 0.000000 GHz
 ATM mode : VC-Mux
 Header Compression : None

Satellite (DVB) Transmitter Status

 State : On (DVB-RCS2)
 IDU Output Power : -19.8 dBm
 Es/No : 14.5 dB
 Header Compression : Disabled
 Timing correction : -299 us (249997 us)
 Frequency correction: 230 Hz

dvb rx show

Satellite (DVB) RX Configuration

 Auto start : Enabled
 Max Traffic MODCOD : 23 16APSK-9/10
 RX watchdog : 15 minute

Idx	Pri	SymbRate[Msps]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name	Enable
* 0	0	25.000000	11.628079	DVB-S2	105	0	0.0 E		Yes	

Satellite (DVB) Receiver Status

 Rx State : On
 DVB State : Forward link up
 Network : 1326, ATI-PI
 Frequency : 11.628125 GHz
 Symbol Rate : 24.999924 Msps
 S2 ModCod
 - receiving : 1 QPSK-1/4
 - current max : 15 8PSK-5/6
 Pilot : On
 Frame length : Short
 DVB S2 Mode : ACM
 DVB S2 Stream type : MPEG-TS
 Roll off : 0.25
 SNR : 11.3 dB
 Input Power : -37 dBm
 # arp show

```

NetAddr   State  MacAddr      If
10.225.0.62 Dynamic 00:0b:ab:f5:c9:62 1
# ip show
Interfaces
If  IPAddress  SubnetMask  BroadCastAddr  MTU      Alias  AdminStatus
1  10.225.0.61 255.255.255.252 10.225.0.63 1500    eth0  1
3  172.18.192.37 255.255.255.255    N/A 1500    dvb0  1
4      N/A      N/A      N/A 1500    air0  1

DNS Client Configuration
Primary DNS Server: 209.244.0.3, Secondary DNS Server: 209.244.0.4

Interface Statistics
----- Input ----- Output -----
If  UCast  NUCast  Disc  Octets  UCast  NUCast  Disc  Octets
1  166167   10  1373 63812278 332013   28   0 438779470
3  325598   0   0 447340706 66405   0   0 56202143
4   0   0   0   0   0   0   0   0
IP Receive Deliver Errors Discards Forward Request NoRoute Discards
491696  160   4   0 399587  262   1  1480

Interface Directed Routing Table
In If Out If

-----IP LAC Statistics-----
RPF  Src eq dest  RPF HitCount  SrceqdestHitCount  MfcHitCount (-1/drop classified)
# device show
System Information:
Name      : ATI-ES-0047-IND
Location   : VARZEA GRANDE PI
Contact    :
System Up time   : 0 days, 00:50:19
CPU Load       : 34%
System time(UTC) : 20 September 2018 14:01:02
Broadcast Message : not set

HW:
Model      : SatLink 2000
HW ID      : 120033
Main board ID : 120026 R6.2

MAC addresses:
Ethernet (LAN) : 00:20:0e:10:8c:c3
Satellite (DVB) : 00:20:0e:10:8c:c3

# dvb tx show

Satellite (DVB) TX Configuration
-----
Auto start      : Enabled
IDU Output Power : -20 dBm
IDU Max Output Power: 0.0 dBm
Default CW Frequency: 0.000000 GHz
ATM mode        : VC-Mux
Header Compression : None

Satellite (DVB) Transmitter Status
-----
State           : On (DVB-RCS2)
IDU Output Power : -19.8 dBm
Es/No           : 14.5 dB
Header Compression : Disabled
Timing correction : -299 us (249997 us)
Frequency correction: 230 Hz
# dvb rx show

```

Satellite (DVB) RX Configuration

 Auto start : Enabled
 Max Traffic MODCOD : 23 16APSK-9/10
 RX watchdog : 15 minute

Idx	Pri	SymbRate[Msp/s]	Freq[GHz]	Mode	PopId	SatId	Pos	SatName	Name	Enable
* 0	0	25.000000	11.628079	DVB-S2	105	0	0.0 E		Yes	

Satellite (DVB) Receiver Status

 Rx State : On
 DVB State : Forward link up
 Network : 1326, ATI-PI
 Frequency : 11.628125 GHz
 Symbol Rate : 24.999924 Msp/s
 S2 ModCod

- receiving : 1 QPSK-1/4
 - current max : 15 8PSK-5/6

Pilot : On
 Frame length : Short
 DVB S2 Mode : ACM
 DVB S2 Stream type : MPEG-TS
 Roll off : 0.25
 SNR : 11.3 dB
 Input Power : -37 dBm

arp show

NetAddr	State	MacAddr	If
10.225.0.62	Dynamic	00:0b:ab:f5:c9:62	1

ip show

Interfaces

If	IPAddress	SubnetMask	BroadCastAddr	MTU	Alias	AdminStatus
1	10.225.0.61	255.255.255.252	10.225.0.63	1500	eth0	1
3	172.18.192.37	255.255.255.255	N/A	1500	dvb0	1
4	N/A	N/A	N/A	1500	air0	1

DNS Client Configuration

Primary DNS Server: 209.244.0.3, Secondary DNS Server: 209.244.0.4

Interface Statistics

----- Input ----- Output -----

If	UCast	NUCast	Disc	Octets	UCast	NUCast	Disc	Octets
1	166167	10	1373	63812278	332013	28	0	438779470
3	325598	0	0	447340706	66405	0	0	56202143
4	0	0	0	0	0	0	0	0

IP	Receive	Deliver	Errors	Discards	Forward	Request	NoRoute	Discards
491696	160	4	0	399587	262	1	1480	

Interface Directed Routing Table

In If Out If

-----IP LAC Statistics-----

RPF	Src	eq	dest	RPF	HitCount	Src	eq	dest	HitCount	MfcHitCount (-1/drop classified)
-----	-----	----	------	-----	----------	-----	----	------	----------	----------------------------------


3 – Configurações dos Equipamentos

Configurações de Rede

Configurações	Interfaces	Roteamento Estático	Roteamento Dinâmico	Configurações IPv6	Controle de Banda	H.A.
<div>+</div> <div>-</div>						
Status	Interface	Endereço	Gateway	Tipo	Zona	Ação
	eth0	10.225.0.62/30	-	Física	WAN	
	eth1	10.225.25.1/24	-	Física	LAN	
	eth2	-	-	Física	-	
	eth3	-	-	Física	-	

```
admin >ifconfig
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.225.0.62 netmask 255.255.255.252 broadcast 10.225.0.63
    ether 00:0b:ab:f5:c9:62 txqueuelen 10000 (Ethernet)
    RX packets 181164 bytes 251008600 (239.3 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 92695 bytes 5061731 (4.8 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
    device memory 0xd0900000-d091ffff

eth1: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.225.25.1 netmask 255.255.255.0 broadcast 10.225.25.255
    ether 00:0b:ab:f5:c9:63 txqueuelen 10000 (Ethernet)
    RX packets 6919 bytes 1553962 (1.4 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 13223 bytes 15186864 (14.4 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
    device memory 0xd0800000-d081ffff
```



4 – Teste de Velocidade -Download/Upload

